


DOWNLIGHT BODO
Adjustable downlight
BOD0630
6 W - 425lm - 4000K



DIMENSIONS	A	B	C
1	46	85	



GENERAL INFORMATIONS	
Code	BOD0630
Ean	8031453025830
Family	DOWNLIGHT BODO
Technology	LED
Body material	PC+AL
Diffuser / lens material	PS
Operating temperature (° C)	-20 - +40

LIGHTING DATA	
Light colour	CW
CCT (K)	4000
Luminous flux (lm)	425
Beam (°)	36
Luminous Efficacy (lm/W)	70,83
Color rendering (CRI)	>80

TECHNICAL FEATURES	
Power (W)	6
Supply voltage (V) / Max (V)	220 / 240
Power frequency (Hz)	50/60
Hole diameter (mm)	75
Current consumption (mA)	47
Insulation class	2
Power factor	0,5
Dimmer compatibility	NO
Nominal life (h)	25000
Impact resistance (IK)	08

PACKAGING	
Packaging	BOX
Pack	20 / 20
Gross weight (Kg)	2.7
Net weight (Kg)	0.1

DOWNLIGHT BODO
Adjustable downlight
BOD0630
6W - 425lm - 4000K

- Recessed LED luminaire in thermoplastic material with integrated power supply
- Lightweight and ideal for false ceilings
- White body in thermoplastic and metal, with satin thermoplastic diffuser
- Adjustable version
- Complete with terminal for simplified wiring

