


YUMA1500
Solar floodlight with separate panel
YUMA1500
10 W - 1500lm - 4000K



DIMENSIONS	A	B	C
1	153	32	144

GENERAL INFORMATIONS	
Code	YUMA1500
Ean	8031453028497
Family	YUMA1500
Technology	LED
Body material	ABS
Diffuser / lens material	PC
Operating temperature (° C)	-15 - +40
Years warranty	2
LIGHTING DATA	
Light colour	CW
CCT (K)	4000
Luminous flux (lm)	1500
Beam (°)	60X120
Luminous Efficacy (lm/W)	130
TECHNICAL FEATURES	
Power (W)	10
Supply voltage (V) / Max (V)	3,7 / 3,7
Current consumption (mA)	3600
Insulation class	3
Power factor	>0,50
Dimmer compatibility	NO
Nominal life (h)	30000

PACKAGING	
Packaging	BOX
Pack	12 / 12
Gross weight (Kg)	14
Net weight (Kg)	1

YUMA1500 Solar floodlight with separate panel

YUMA1500

10W - 1500lm - 4000K

- Floodlight with dusk sensor and PIR presence detector
- Easy installation: mains connection not needed
- High quality Li-on 18650 battery, 3.7V, 3600mAh, 13.32Wh
- Floodlight can be separated from the solar panel for standalone use
- High efficiency 150 lm/W
- Wide illumination area, 120° x 60° asymmetric beam angle
- Self-extinguishing ABS + PC anti UV material
- IP67 connector, 5m cable
- Remote control included
- 2 operating modes



OPERATION

The floodlight has two working modes, selectable with the remote control.

AUTO SENSOR MODE: the floodlight automatically lights up at night and turns to full brightness when motion is detected in the range <8m, then turns to lower brightness in 60 seconds of no motion.

KEEP LIGHTING MODE: the floodlight automatically lights up at night and keep selected brightness (3h, 5h or 8h). When the battery is less than 30%, lamp turns to auto sensor mode.

