


**DOWNLIGHT BODO**  
**Adjustable downlight**  
**BODO2020**  
20 W - 1530lm - 3000K



DIMENSIONS	A	B	C
1	84	140	



GENERAL INFORMATIONS	
Code	BODO2020
Ean	8031453026011
Family	DOWNLIGHT BODO
Technology	LED
Body material	PC+AL
Diffuser / lens material	PS
Operating temperature (° C)	-20 - +40
Years warranty	2
LIGHTING DATA	
Light colour	WW
CCT (K)	3000
Luminous Jux (lm)	1530
Beam (°)	36
Luminous Efficacy (lm/W)	76,5
Color rendering (CRI)	>80

TECHNICAL FEATURES	
Power (W)	20
Supply voltage (V) / Max (V)	220 / 240
Power frequency (Hz)	50/60
Hole diameter (mm)	125
Current consumption (mA)	88
Insulation class	2
Power factor	0,9
Dimmer compatibility	NO
Nominal life (h)	25000
Impact resistance (IK)	08
PACKAGING	
Packaging	BOX
Pack	20 / 20
Gross weight (Kg)	7.3
Net weight (Kg)	0.27

**DOWNLIGHT BODO**  
**Adjustable downlight**  
**BODO2020**  
20W - 1530lm - 3000K

- Recessed LED luminaire in thermoplastic material with integrated power supply
- Lightweight and ideal for false ceilings
- White body in thermoplastic and metal, with satin thermoplastic diffuser
- Adjustable version
- Complete with terminal for simplified wiring

