

SPIKY1

MANUALE D'USO E INSTALLAZIONE USE AND INSTALLATION MANUAL

INTRODUZIONE - INTRODUCTION

Picchetto da giardino con portalamпада GU10 in alluminio pressofuso
GU10 lampholder die-casting aluminum spike light.



CARATTERISTICHE TECNICHE - TECHNICAL CHARACTERISTICS

MODELLO MODEL	Colore Colour	Volt	Hz	Attacco lampada Lampholder	Dimensioni Dimensions (mm)	Temperatura di lavoro Working Temperature	Protezione IP IP Protection
SPIKY1	GRIGIO ANTRACITE <i>Dark Grey</i>	220-240V ~	50/60Hz	GU10	266x109x60	-15 +45°C	IP65
SPIKY1C	CORTEN <i>Corten</i>	220-240V ~	50/60Hz	GU10	266x109x60	-15 +45°C	IP65

ISTRUZIONI DI INSTALLAZIONE – INSTALLATION INSTRUCTION

1. Prima di iniziare assicurarsi di aver tolto tensione all'impianto elettrico.
 2. Montare il picchetto al faretto
 3. Posizionare il faro nel punto voluto
 4. Preparare il connettore stagno
 5. Effettuare il collegamento dei cavi elettrici
 6. Assicurarsi che le due parti siano serrate
 7. Inserire lampada GU10 e fissare la copertura avvitando il corpo diffusore
-
1. *Switch off the power before starting*
 2. *Assemble the spike to the spotlight*
 3. *Insert the spike into the ground in the desired place*
 4. *Prepare the waterproof connector*
 5. *Connect the cable*
 6. *Be sure that both sides are tightened*
 7. *Insert the GU10 bulb and secure the cover to the fixture screwing diffusor body.*

