


DOWNLIGHT BODO CCT



POTENZA W	KELVIN	LUMEN lm	MISURE mm	FASCIO °	CODICE	EAN	CLASSE ENERGETICA
4	3000-4200-6500	380	1	100	B0D04	8031453025779	A ↑ G F
8	3000-4200-6500	780	2	100	B0D08	8031453025786	A ↑ G F
16	3000-4200-6500	1700	3	100	B0D016	8031453025793	A ↑ G F
20	3000-4200-6500	2150	4	100	B0D020	8031453025809	A ↑ G F
24	3000-4200-6500	2650	5	100	B0D024	8031453025816	A ↑ G F



DIMENSIONI	A	B	C
1	36	90	
2	46	115	
3	48	165	
4	50	190	
5	50	215	

- APPARECCHIO A LED DA INCASSO IN MATERIALE TERMOPLASTICO CON ALIMENTATORE INTEGRATO
- LEGGERI ED IDEALI PER CONTROSOFFITTI
- CORPO BIANCO IN TERMOPLASTICA E METALLO, CON DIFFUSORE IN TERMOPLASTICO SATINATO ANTI ABBAGLIAMENTO
- COMPLETO DI MORSETTO PER UN CABLAGGIO SEMPLIFICATO
- CCT SELEZIONABILE