


# OVIEDO ROUND

## Ceiling lamp

OVIEDO24R

22 W - 2350lm - 3000-4200-6500K



DIMENSIONS	A	B	C
1	78	220	

GENERAL INFORMATIONS	
Code	OVIEDO24R
Ean	8031453025670
Family	OVIEDO ROUND
Technology	LED
Body material	PC
Diffuser / lens material	PC
Operating temperature (° C)	-20 - +40

PACKAGING	
Packaging	BOX
Pack	20 / 20
Gross weight (Kg)	8.3
Net weight (Kg)	0.4

LIGHTING DATA	
Light colour	CCT
CCT (K)	3000-4200-6500
Luminous flux (lm)	2350
Luminous Flux Module (lm)	2900
Beam (°)	120
Luminous Efficacy (lm/W)	80
Color rendering (CRI)	>80

TECHNICAL FEATURES	
Power (W)	22
Supply voltage (V) / Max (V)	220 / 240
Power frequency (Hz)	50/60
Insulation class	2
Power factor	>0,5
Dimmer compatibility	NO
Nominal life (h)	30000
Impact resistance (IK)	08

## OVIEDO ROUND

### Ceiling lamp

OVIEDO24R

22W - 2350lm - 3000-4200-6500K

- Round ceiling lamp with high resistance PC diffuser IK08
- Easy to apply, ideal for outdoors (e.g. under porticos, terraces, balconies)
- Both wall and ceiling installation
- Modern and linear design, available in two sizes
- Selectable CCT
- Also available in variant with dusk sensor with intervention A  $\leq$  30lux
- White and black rings included

