

DOWNLIGHT BODO



| POTENZA W | KELVIN | LUMEN lm | MISURE mm | FASCIO ° | CODICE | EAN | CLASSE ENERGETICA |
|--------------|--------|-------------|--------------|-------------|----------|---------------|-------------------|
| 6 | 3000 | 425 | 1 | 36 | BOD0620 | 8031453025823 | A ↑ G |
| 6 | 4000 | 425 | 1 | 36 | BOD0630 | 8031453025830 | A ↑ G |
| 20 | 3000 | 1530 | 2 | 36 | BOD02020 | 8031453026011 | A ↑ F |
| 20 | 4000 | 1530 | 2 | 36 | BOD02030 | 8031453026028 | A ↑ F |

IP 20

IK 08

-C
220-240V




h
25.000

°
-20°+40°



| DIMENSIONI | A | B | C |
|------------|----|-----|---|
| 1 | 46 | 85 | |
| 2 | 84 | 140 | |



- APPARECCHIO A LED DA INCASSO IN MATERIALE TERMOPLASTICO CON ALIMENTATORE INTEGRATO
- LEGGERI ED IDEALI PER CONTROSOFFITTI
- CORPO BIANCO IN TERMOPLASTICA E METALLO, CON DIFFUSORE IN TERMOPLASTICO SATINATO
- VERSIONE ORIENTABILE
- COMPLETO DI MORSETTO PER UN CABLAGGIO SEMPLIFICATO